





Main data for Solenoid actuators

Type	Symbol	Voltage	Load		Connection	Weight kg	Order code
Complete units, solenoid and cable plug							
		24 V ~ 50/60 Hz	8,5 VA	Manual override	22 mm Plug-in	0,17	**PRS-A121B**
		24 V	6 W	Manual override	22 mm Plug-in	0,17	**PRS-A122B**
		115 V ~ 50 Hz 120 V ~ 60 Hz	8,5 VA	Manual override	22 mm Plug-in	0,17	**PRS-A121F**
		230 V ~ 50 Hz 240 V ~ 60 Hz	8,5 VA	Manual override	22 mm Plug-in	0,17	**PRS-A121M**
Solenoid mounting base							
		For mounting the solenoid coil and plunger on 3-port modular sub-bases type PZU-A••, see page 18		Manual override		0,09	**PRS-D10**
Solenoid coil with plunger and 22 mm plug-in connector (4)		24 V*	6 W			0,135	**PVA-F102B**
		48 V*	6 W			0,135	**PVA-F102E**
		24 VAC 50/60 Hz	8,5 VA			0,135	**PVA-F101B**
		48 VAC 50/60 Hz	8,5 VA			0,135	**PVA-F101E**
		115 VAC 50 Hz/ 120 VAC 60 Hz	8,5 VA			0,135	**PVA-F101F**
		230 VAC 50 Hz 240 VAC 60 Hz	8,5 VA			0,135	**PVA-F101M**
		255 VAC 50 Hz	8,5 VA			0,135	**PVA-F101U**

* Versions available for operation in explosive atmospheres.
- Conforming to certificate LCIE 866115X
- Electrical equipment conforming to harmonised European standards

EN 50014 dated March 1977 (NFC 23514 dated May 1982)
EN 50019 dated March 1977 (NFC 23519 dated May 1982)
- Referencing code EExe II T4 (consult Technical Sales Department)
(4) Can be fitted with LED indicator and suppression, PVA•ZF••

Main data for Pressure switches

Type	Symbol	Electrical characteristics	Pneumatic characteristics		Connection Electric/Pneumatic	Weight kg	Order code
Complete unit with sub-base, solenoid and cable plug							
		N/O contact	override	Manual Plug-in	22 mm Ø4 mm Swivel push-in	0,13	**PRE-A12**
Without sub-base							
		N/O contact		Manual override	22 mm Plug-in Ø4 mm Swivel push-in	0,04	**PRE-A10**
Line mounted							
		1 CO contact 5 A/250 V	Fixed operating threshold	Manual override	Ø4 mm Push-in	0,05	**PS1-P1081**
		1 CO contact 5 A/250 V	Adjustable operating threshold	Manual override	Ø4 mm Push-in	0,05	**PS1-P1091**

Indicates stocked product.